

## **SUPER-STICK**

### **DESCRIPTION**

SUPER-STICK is a special liquid additive that enhances the adhesion of an epoxy resin to certain substrates. The addition of SUPER-STICK to only the prime coat is highly recommended when applying an epoxy coating or an epoxy flooring system on ceramic tile, quarry tiles, brick pavers, existing epoxy, urethane, etc.

### **BENEFITS**

- To increase adhesion to existing polymer floors.
- To increase adhesion to quarry or ceramic tile.

### **MIXING INFORMATION**

Add SUPER-STICK to the resin portion of DUR-A-GLAZE #4 or to the blended hardener and resin. The small amount of the additive will not disturb the proper ratio of the hardener and resin blend. Add up to 3 ounces of SUPER-STICK to every gallon of mixed epoxy. Blend thoroughly.

### **LIMITATIONS**

SUPER-STICK is used as a bonding agent in situations where TIE-COAT cannot be used. TIE-COAT gives the best adhesion of any polymer system to existing epoxies, urethanes, tile etc. Use of this product is not a substitute for adequate preparation. Please refer to the master "Surface Preparation Guide" for more information.

### **PACKAGING**

SUPER-STICK is available in 1-pint cans, 1-quart cans, 1-gallon cans and 5-gallon pails.

### **CAUTION**

**Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN.**

*Before using any DUR-A-FLEX, Inc. product, be sure the Material Safety Data Sheet is read and understood.*