

## CRYL-A-FLEX™

**CRYL-A-FLEX™** commercial/industrial floor coatings and overlays are based on 100% reactive, fast curing, high strength, methyl methacrylate (MMA) based acrylic reactive resins. The product line is VOC compliant (<100 g/L), UV stable, impact and abrasion resistant, non-porous and impervious. These flooring systems will not chalk, crack or age-harden. They achieve full cure and chemical resistance in one hour and can be installed below freezing. All CRYL-A-FLEX resins are available with Bio-Pruf® antibacterial and fungal additive.

**CRYL-A-SHIELD™** Clear coating/sealer 12-50 mils (0.25-1.25 mm)

- 1 coat of Cryl-A-Prime.
- 1 or 2 coats of clear Cryl-A-Top or Cryl-A-Prime.
- Surface finish can be smooth or slip resistant.

**CRYL-A-STAIN** Stain/dyed look sealer with all the advantages of MMA. 30-45 mils (0.5-1.25 mm)

- 1 coat Cryl-A-Prime clear or tinted
- 1-2 coats of Cryl-A-Top clear or tinted

**CRYL-A-FLOOR™** Solid color broadcast system. 1/8 -3/16 inch (3-5 mm)

- 1 coat of Cryl-A-Prime.
- 2 coats of pigmented Cryl-A-Glaze with aggregate broadcast to excess into each coat.
- 2 pigmented topcoats of Cryl-A-Top.

**CRYL-A-FLOOR SL™** Self-leveling overlay with aggregate broadcast and topcoats. 3/16-1/4 inch (4-6 mm)

- 1 coat of Cryl-A-Prime.
- 1 coat Cryl-A-Glaze, SL Filler Blend, pigment with Flintshot or Q-Rok broadcast.
- 2 pigmented topcoats of Cryl-A-Top.

**CRYL-A-QUARTZ™** Multi-colored quartz broadcast system. 1/8 - 3/16 inch (3-5 mm)

- 1 coat of Cryl-A-Prime.
- 2 coats of Cryl-A-Glaze with Dur-A-Quartz (Q-28 or Q-11) broadcast to excess into each coat.
- 2 clear topcoats of Cryl-A-Top

**CRYL-A-QUARTZ SL™** Self-leveling overlay with colored quartz aggregate broadcast and topcoats.

- 3/16-1/4 inch (4-6 mm)
- 1 coat of Cryl-A-Prime.
- 1 coat Cryl-A-Glaze, SL Filler Blend, pigment with Q-28 or Q-11 colored quartz broadcast.
- 2 clear topcoats of Cryl-A-Top.

**CRYL-A-CHIP™** Multi-colored decorative broadcast chip system. 1/16 inch (1.6 mm)

- 1 coat of Cryl-A-Prime.
- 2 coats of Cryl-A-Glaze with decorative colored chips broadcast to excess into each coat.
- 2 topcoats of Cryl-A-Top.

**CRYL-A-CHIP SL™** Self-leveling overlay with decorative colored chips broadcast and topcoats. 3/16 inch (4 mm)

- MICRO – MACRO decorative chips
- 1 coat of Cryl-A-Prime.
- 1 coat Cryl-A-Glaze, pigmented SL Filler Blend, decorative color chip broadcast.
- 2 clear topcoats of Cryl-A-Top.

**CRYL-A-WALL VC** Multi-colored decorative broadcast chip system for walls 1/16 inch (1.6 mm)

- MICRO-MACRO decorative chips
- 1 coat Cryl-A-Prime
- 2 coats of Cryl-A-Glaze with decorative chips broadcast into each coat
- 2 or 3 topcoats of Cryl-A-Top

**CRYL-A-TEX™** Polymer Concrete for deep patching, sloping and structural repairs.

- 1/4 - 6 inches (6- 150 mm) plus.
- 1 coat of Cryl-A-Prime.
- 1 layer of Cryl-A-Tex. This system can be extended with the addition of clean and dry special aggregate.