



DUR-A-FLEX
INNOVATION FROM THE FLOOR UP

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION	HAZARD RATING	Health	2
	0 = Least	Flammability	3
	1 = Slight	Reactivity	2
	2 = Moderate	Personal Protection	G
3 = High			
4 = Extreme			
IDENTITY (As Used on Label)	Cryl-A-Tex Liquid/LM Liquid		
COMMON NAME	Acrylic Resin Solution		

SECTION II - PRODUCT COMPONENTS	CAS.#	OSHA PEL	ACGIH TLV
Methyl Methacrylate	80-62-6	100 ppm	100 ppm
1,3 Butanediol Dimethacrylate	1189-08-8	N.E. ¹	N.E.
White Mineral Oil	8042-47-5	5 mg/m ³	5 mg/m ³
Dimethyl-p-Toluidine	99-97-8	N.E.	N.E.
2-Ethylhexyl Acrylate	103-11-7	N.E.	N.E.

¹ N.E. = None Established

Warning: This material is highly flammable. Direct contact can cause severe irritation to the eyes, skin and respiratory tract. Inhalation and skin contact can cause an allergic sensitization. Inhalation of high vapor concentrations can cause headache, nausea, drowsiness and unconsciousness.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point °F	212 (MMA)	Specific Gravity (H ₂ O = 1)	approx. 1
Vapor Pressure (mm Hg)	30 (MMA)	Melting Point	N/A
Vapor Density (AIR = 1)	>1 (MMA)	Evaporation rate (Butyl Acetate = 1)	>1
Volatile Organic Compounds (VOC) = Zero grams/liter			
Solubility in Water	16 g/l (MMA)		
Appearance and Odor	Low viscosity, Moderately turbid fluid with a sweet ester odor		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	50 °F	Flammable Limits	LEL	UEL
			2.10%	12.50%

Extinguishing Media Use water mist, CO₂, foam, dry powder or cover with sand

Special Firefighting Procedures

Evacuate enclosed and surrounding areas. If smoke and fumes cannot be avoided, use proximity suit and self-contained breathing apparatus. Use water spray to cool containers and disperse vapors. Keep spills away from sources of ignition.

Unusual Fire and Explosion Hazards

Vapor is heavier than air and forms explosive mixture with air. Never use welding or cutting torch on or near containers or drums (even when empty). Product residue or vapor in drum or container can ignite explosively.

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Keep containers closed when not in use.
Incompatibility (Materials to Avoid)	Reducing agents, Oxidizing agents, solid polymeric particles		
Hazardous Decomposition or Byproducts	Thermal decomposition may yield water, oxides of carbon, and acid fumes		
Hazardous Polymerization	May Occur	X	Conditions to Avoid: High temperatures, oxygen-free atmospheres, or contaminated areas. Avoid contact with peroxides, azocompounds and redox systems.
	Will Not Occur		

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Inhalation and skin contact can lead to an allergic respiratory sensitization. Persons may experience rapid irritation of skin upon exposure.

Persons with lung disorders or who are sensitized should not use this product.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure

Conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - May cause burns to the respiratory tract. Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing. Consult physician.

INGESTION - Expected to be slightly toxic by ingestion. May cause burns to the gastrointestinal tract. If swallowed, induce vomiting immediately as directed by a physician. Get medical attention immediately.

Never give liquids to an unconscious or convulsing person.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves	Natural rubber or Neoprene.	Eye Protection	Splash goggles or face shield.
-------------------	-----------------------------	----------------	--------------------------------

Other Protective Clothing or Equipment:

Use rubber apron, face shield and appropriate clothing to prevent contact with skin. Launder contaminated clothing before reuse. Discard contaminated leather shoes and canvas sneakers. Protective skin creams help cleaning with soap and water, gloves must still be worn. An eye wash station or an adequate supply of clean water must be available at work area.

Work/Hygienic Practices Establish good personal hygiene and work practices. Always wash hands and face before eating, drinking or smoking.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled: Wear protective equipment to prevent exposure. Stop spill and dike with sand or earth to prevent spreading. Avoid ignition sources. Absorb with sand or other non-flammable absorbent material and transfer to approved DOT drum for recovery or disposal. CERCLA/SARA requires notification of the appropriate Federal, State and Local authorities of releases of hazardous or extremely hazardous quantities equal to or greater than the reportable quantities (RQs) 40 CFR 302.4 and 40 CFR 355. SARA Title 313 requires submission of annual reports of releases of toxic chemicals that appear in 40 CFR 372. Components present in this product at a level which could require reporting are listed in section XII.

Waste Disposal Method: This material is a hazardous waste (as per RCRA) because of its ignitability. Disposal should be conducted by an EPA or (RCRA) permitted Facility. CERCLA Reporting: Methyl Methacrylate (MMA) RQ=1000# SARA Title 313 reporting MMA

Precautions to be Taken in Handling and Storing:

Store in cool, dry, well-ventilated area away from sources of ignition. Keep containers tightly closed when not in use.

Other Precautions DO NOT THIN THIS PRODUCT

Prepared By: Samet Dy - Chemist

PLEASE NOTE "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



DUR-A-FLEX
INNOVATION FROM THE FLOOR UP

95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2010

SECTION I - IDENTIFICATION	HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	3
		Flammability	0
		Reactivity	0
		Personal Protection	F
IDENTITY (As Used on Label) Cryl-A-TEX Powder			
COMMON NAME: Polymer concrete sand blend			

SECTION II - PRODUCT COMPONENTS	CAS.#	OSHA PEL	ACGIH TLV
Crystalline Silica (Quartz) ¹	14808-60-7	10mg/m ³	0.1 mg/m ³
		%SiO ₂ +2	
Inert ingredients	Proprietary ²	15 mg/m ³	10 mg/m ³
Acrylic polymer	Proprietary	100 ppm	100 ppm
Wetting agent	Proprietary	3 mg/m ³	3 mg/m ³
Rutile titanium dioxide	13463-61-7	15 mg/m ³	10 mg/m ³
Inorganic iron oxides	1309-37-1	15 mg/m ³	10 mg/m ³

¹Crystalline silica can be a lung injury and cancer hazard. Do not breathe dust. May cause delayed lung injury. Long term exposure can cause silicosis, a respiratory disease which can result in a delayed, disabling, and sometimes fatal lung injury.

Crystalline silica inhaled from occupational sources can from occupational sources can cause cancer in humans. Risk of injury is dependent on the duration and level of exposure.

²The manufacturer of the component states that they will provide additional information to a health professional in the event of a medical emergency.

T.S.C.A. Status - O.K. on all above components.

FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point °F	N/A	Specific Gravity (H ₂ O = 1)	approx. 1.51
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC) = Zero grams/liter			
Solubility in Water	Negligible		
Appearance and Odor	Colored sand with no significant odor		

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)		Flammable Limits	LEL	UEL
Fully oxidized, will not burn	N/A		N/A	N/A
Extinguishing Media	Compatible with all extinguishing media. Use any media appropriate for the surrounding fire.			
Special Firefighting Procedures	N/A			
Unusual Fire and Explosion Hazards	N/A			

SECTION V - REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	None
Incompatibility (Materials to Avoid)	Reducing agents, strong oxidizers, acids, alkalis, and accelerators		
Hazardous Decomposition or Byproducts	Oxides of carbon		
Hazardous Polymerization	May Occur		Conditions to Avoid:
	Will Not Occur	X	This material can initiate polymerization reactions with other organic materials

SECTION VI - HEALTH HAZARD DATA

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	YES	YES	YES

Signs and Symptoms of Exposure Irritation of skin.

Health Hazards (Acute and Chronic)

ACUTE - Irritation of skin and dermatitis.

CHRONIC - Excessive inhalation of dust may result in respiratory disease such as silicosis, pulmonary fibrosis, ect.

The IARC has evaluated in vol. 42(monographs) that there is "sufficient evidence for the carcinogenicity of crystalline silica dust to experimental animal" and "limited evidence" with respect to humans.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	Yes (Respirable Quartz)	Yes*level 2A grouping	NO

Medical Conditions Generally Aggravated by Exposure

Lung disorders and persons subject to eye irritation.

Emergency and First Aid Procedures

EYES - Flush with water, holding lids open for 15 minutes or more. Call physician for advice if necessary.

SKIN - PROMPTLY wash with soap and water. DO NOT wash with solvents. Seek medical advice if irritation develops or persists.

INHALATION - Move person to fresh area if effects occur. If needed, give oxygen or artificial respiration to improve breathing . Consult physician.

INGESTION - Expected to be slightly toxic by ingestion. If swallowed, induce vomiting immediately as directed by a physician.

Get medical attention immediately. Never give liquids to an unconscious or convulsing person.

OTHER HEALTH EFFECTS - Medical conditions which may be aggravated by exposure to this product include, conjunctivitis of the eye, dermatitis of the skin, asthma and respiratory diseases.Sensitization may occur by skin contact.

****NOTE**** persons with lung disorders or who are sensitized should not use this product.

SECTION VII - CONTROL MEASURES

Respiratory Protection (Specify Type): Atmospheric levels should be maintained below the exposure limits listed in section II by using engineering controls. Provide adequate exhaust ventilation and/or NIOSH approved cartridge respirator.

Ventilation	Local Exhaust	If needed.	Special	None known.
	Mechanical	Adequate exhaust ventilation must exhaust AWAY from applicator.		

Protective Gloves	Natural rubber or Neoprene.	Eye Protection	Splash goggles or face shield.
-------------------	-----------------------------	----------------	--------------------------------

Other Protective Clothing or Equipment

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product. Refer to the most recent standards of ANSI (Z88.2), OSHA (29 CFR 1910.134), MSHA (30 CFR Parts 56 and 57), and NIOSH Respirator Decision Logic. Maintain, clean and fit test respirators in accordance with OSHA regulations.

Work/Hygienic Practices Avoid creating and breathing dust.

SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled

Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Avoid creation of respirable dust

Waste Disposal Method:

Dispose in accordance with Federal, State and Local requirements.

Avoid creation of respirable dust. Take precaution against bag breakage

Other Precautions NONE KNOWN.

Prepared By: Samet Dy - Chemist

**PLEASE
NOTE**

"The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."



95 Goodwin Street, East Hartford, CT., 06108 (860) 528-9838

Material Safety Data Sheet

Date Prepared 8/2/2011

SECTION I - IDENTIFICATION	HAZARD RATING 0 = Least 1 = Slight 2 = Moderate 3 = High 4 = Extreme	Health	2
		Flammability	2
		Reactivity	3
		Personal Protection	E
IDENTITY (As Used on Label) Cryl-A-Cure			
COMMON NAME Benzoyl Peroxide; Dibenzoyl Peroxide; BPO			

SECTION II - PRODUCT COMPONENTS	CAS.#	OSHA PEL	ACGIH TLV
Benzoyl Peroxide - (BPO)	94-36-0	5 mg/m ³	5 mg/m ³
Dicyclohexylphthalate	84-61-7	N.E. ¹	N.E.

¹Not Established
Benzoyl peroxide is subject to SARA title III, section 313 reporting requirement.

Shipping Description: Organic Peroxide Type D Solid (dibenzoyl peroxide, 50%) 5.2, UN3106, PG II
North American Emergency Response Guide No. :145

Required Labels: Organic Peroxide.
Environ. Hazardous Substance: This product does not contain an environmentally hazardous substance per 49CFR 172.101 appendix A.

T.S.C.A. Status - O.K. on all above components.
FOR SPILL, LEAK, FIRE, OR ACCIDENT, CALL CHEMTREC 24-HOUR EMERGENCY NUMBER 1-800-424-9300

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point °F	N/A	Specific Gravity (H ₂ O = 1)	N/A
Vapor Pressure (mm Hg)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation rate (Butyl Acetate = 1)	N/A
Volatile Organic Compounds (VOC) = Zero grams/liter		Molecular Weight	242.2
Solubility in Water INSOLUBLE			
Appearance and Odor White granules with slight odor			

SECTION IV - FIRE and EXPLOSION HAZARD DATA

Flash Point (Closed Cup Method)	N/A	Flammable Limits	LEL	UEL
			N/A	N/A

Extinguishing Media **Use water mist, CO₂, foam, or dry powder.**
Special Firefighting Procedures

Evacuate area and apply water from a safe distance. Spray water on the nearby peroxide containers to prevent overheating. Use self-contained, positive pressure/pressure demand respirators.

Unusual Fire and Explosion Hazards
Peroxides and decomposition products are flammable and can ignite with explosive force if confined.

SECTION V - REACTIVITY DATA

Stability	Unstable	X	Conditions to Avoid Keep containers closed when not in use.
	Stable		
Incompatibility (Materials to Avoid) Peroxides, amines, sulfur compounds, heavy metal ions and alkalis			
Hazardous Decomposition or Byproducts Oxides of Carbon and Biphenyl			
Hazardous Polymerization	May Occur	X	Conditions to Avoid: Hazardous conditions to avoid that could cause decomposition are extensive heat or contaminated with incompatible materials.
	Will Not Occur		

