



**SECTION VI - HEALTH HAZARD DATA**

Route(s) of Entry:	Inhalation?	Skin?	Ingestion?
	Yes	Yes	Yes

Signs and Symptoms of Exposure	Temporary Inhalation Discomfort.
--------------------------------	----------------------------------

Health Hazards (Acute and Chronic)

ACUTE - None known other than possible temporary discomfort due to inhalation of dust concentration.

CHRONIC - NONE KNOWN.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	NO	NO	NO

Medical Conditions Generally Aggravated by Exposure	None Known.
---	-------------

Emergency and First Aid Procedures

EYES - hold eyes apart and flush with clean water for 15 minutes. If irritation or redness develops and persists seek medical attention.

SKIN - May Cause skin dryness or cracking. Wash Thoroughly with soap and water.  
Seek medical attention if redness swelling, itching, or burning occurs.

INHALATION - For inhalation discomfort move person to fresh air.

INGESTION - Do not induce vomiting. If conscious, give several glasses of water. Never give anything by mouth to an unconscious person.

**SECTION VII - CONTROL MEASURES**

Respiratory Protection (Specify Type)

Provide adequate exhaust ventilation; use a NIOSH - approved respirator if PELS/TLVS are exceeded.

Ventilation	Local Exhaust	If necessary.	Special	None Known
	Mechanical	Adequate for dusty environments		

Protective Gloves	Not necessary.	Eye Protection	Safety goggles, do not wear contact lenses.
-------------------	----------------	----------------	---

Other Protective Clothing or Equipment

NONE KNOWN.

Work/Hygienic Practices	Avoid unnecessary formation of dust.
-------------------------	--------------------------------------

**SECTION VIII - PRECAUTIONS FOR SAFE HANDLING AND USE**

Steps to be Taken in Case Material is Released or Spilled

No - Sag #2 may be swept up or vacuumed for normal disposal.

Waste Disposal Method

No - Sag #2 is not a hazardous waste under U.S. Federal RCRA Regulations.

Precautions to be Taken in Handling and Storing	Proper precautions should be taken when using No-Sag #2 in the presence of flammable or explosive liquids. (See NFPA - 77 Static Electricity).
---	--

Other Precautions	Dry powders can build static charges when subjected to friction.
-------------------	--

Prepared by	Samet Dy - Urethane Chemist
-------------	-----------------------------

**PLEASE NOTE** "The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND DISCLAIMS ALL LIABILITY FOR RELIANCE THEREON. User should satisfy himself that he has all current data relevant to his particular use."