

## **SUPER-STICK**

### **DESCRIPTION**

SUPER-STICK is a special liquid additive that enhances the adhesion of an epoxy resin to certain substrates. The addition of SUPER-STICK to only the prime coat is highly recommended when applying an epoxy coating or an epoxy flooring system on ceramic tile, quarry tiles, brick pavers, existing epoxy, urethane, etc.

### **BENEFITS**

- To increase adhesion to existing polymer floors.
- To increase adhesion to quarry or ceramic tile.

### **LIMITATIONS**

Use of this product is not a substitute for adequate preparation. Please refer to the master "Surface Preparation Guide" for more information.

### **PACKAGING**

SUPER-STICK is available in 1-pint cans, 1-quart cans, 1-gallon cans and 5-gallon pails.

### **MIXING INFORMATION**

Add SUPER-STICK to the resin portion of DUR-A-GLAZE #4 or to the blended hardener and resin. The small amount of the additive will not disturb the proper ratio of the hardener and resin blend. Add 2 ounces of SUPER-STICK to every 1-1/2 gallons of mixed epoxy. Blend thoroughly.

### **CAUTION**

**Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN.**

#### **IMPORTANT!**

*Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.*

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT [DUR-A-FLEX.COM](http://DUR-A-FLEX.COM) FOR THE LATEST VERSION