

FLINTSHOT, Q-ROK, F-60 QUARTZ AGGREGATE

DESCRIPTION

DUR-A-QUARTZ FLINTSHOT is a naturally rounded, translucent quartz aggregate produced specially for seamless polymer flooring applications. The very hard quartz granules are sieved for a selected size range.

DUR-A-QUARTZ Q-ROK is an aggregate produced specifically for seamless polymer flooring where a high degree of slip resistance is desired. The base material is a naturally formed, semi-angular, very hard quartz granule. The material is cleaned, dried and sieved for a selected size range.

DUR-A-QUARTZ F-60 is a naturally-rounded, whole grain sand sized for consistent particle size and distribution. It is commonly used as a filler in troweled or self-leveling aggregate blends.

HARDNESS 6.5 - 7 on Moh's Mineral Scale

POROSITY less than 2.0%

MOISTURE CONTENT less than 0.5%

PACKAGING Flintshot: 50 and 100 lbs. bags; Q-Rok and F-60: 100 lb. bags,

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN. Before using any Dur-A-Flex products, be sure the Safety Data Sheet is read and understood.

SIEVE ANALYSIS

(Typical Analysis- Not Specifications)

<u>U.S.</u> <u>Mesh</u>	<u>FLINTS</u> <u>HOT</u> <u>Quartz</u>	<u>Q-ROK</u> <u>Quartz</u>	<u>F-60</u>	<u>Special</u> <u>Bond</u>
16	---	0.4	---	---
---	---	---	---	---
20	<1	76	---	---
30	23	15	---	---
40	70	3	1	3.0
50	6	1	22	21.5
70	<1	<1	38	34.1
100	---	---	30	28.3
140	---	---	8	11.0
200	---	---	1	1.9
270	---	---	---	0.1

Before using any Dur-A-Flex, Inc. product, be sure the Material Safety Data Sheet is read and understood.