

## CRYL-A-TEX

### DESCRIPTION

CRYL-A-TEX is a 100% reactive, fast curing, high strength; methyl methacrylate (MMA) based polymer concrete. It is a three-component mortar consisting of a MMA liquid component, a powder component made from sands and fillers, and CRYL-A-CURE (BPO), which initiates the cure. The mortar can be extended with washed and dried pea gravel to produce a polymer concrete for deeper applications. This system cannot be thinned with solvents.

### BENEFITS

- VOC compliant, < 100 g/L
- Fast cure, full strength in 1 - 1½ hours
- Indoor and outdoor applications
- Resistant to chemical attack
- Seamless, no cold joints, always bonds to itself
- Meets USDA/FDA and CFIA requirements
- Use over a wide temperature range, 0°F to 90°F

### LIMITATIONS

Products are to only be installed at minimum thickness, temperature and guidelines as given in Application Instructions.

### TYPICAL USES

- Repair potholes, spalled and eroded concrete
- Bridge, highway and runway repair
- Rebuild pump bases
- Overlays
- Vertical surfaces, form
- Rebuild joints
- Structural repairs
- Sloping
- Grouting
- Anchor bolts

### COLORS

CRYL-A-TEX is available in Natural but can be pigmented with 4 fluid ounces of CRYL-A-COLOR. Refer to the Standard Color Chart on our website.

### PACKAGING & STORAGE CONDITIONS

CRYL-A-TEX LIQUID is available in 1-gallon cans, 5-gallon pails and 50-gallon drums. CRYL-A-TEX POWDER is available in 31 lb bags.

Store in a cool and dry place below 85°F and out of direct sunlight. Do not store near open flame or food. The shelf life is 6 months from ship date in the original unopened containers.

### SURFACE PREPARATION

Use a shot blaster or surface grinder to achieve a CSP of 2-3, ensure the surface is clean, dry, and free of all contaminants before you begin applying the system. Always honor moving joints and fill static joints as part of the preparation step. Refer to the master Surface Preparation and Joint Guidelines Guide at DUR-A-FLEX.COM for more information.

### APPLICATION METHOD / SPREAD RATE

Refer to the Application Instructions for complete details on our website.

### DRAWINGS AND DETAILS

Standard CAD drawings and details are available for coves, drains, breaches, transitions, etc. on our website.

### JOINT GUIDELINES

Refer to the Joint Guidelines for complete details on our website

### MOISTURE CONCERNS

Core Analysis Testing is available from Dur-A-Flex to help provide a measurement of ionic content in flooring substrate. Please refer to the Floor Evaluation Guidelines or visit DUR-A-FLEX.COM for more information.

### BOND TEST

Prior to full application of the primer, bond tests should be conducted to determine adequacy of substrate preparation and bond. Refer to the Application Instructions for complete details on our website.

### CURE

CRYL-A-TEX system will cure typically in 1½ hours depending on temperature. At this time the polymer concrete is fully functional or ready for subsequent applications.

### PHYSICAL CHARACTERISTICS

Percent Reactive	100%
VOC	<100 g/L
Cure Rate @ 68°F (20°C)	1-1½ hour
Tensile Strength	1,000-1,200 psi (6.9-8.3 mpa)
Compressive Strength	7,000-9,000 psi (48-62 N/mm <sup>2</sup> )
Flexural Strength	2,200-2,800 psi (15-19 N/mm <sup>2</sup> )

## **CAUTION**

**CRYL-A-TEX LIQUIDS are flammable liquids in their uncured state. Smoking, open flames or sparks should not be permitted during the handling of the product.**

Workers should wear protective clothing consisting of splash-proof goggles, impermeable gloves and, where exposure limits are exceeded, an organic vapor respirator should be used.

Air powered or explosion proof mixing equipment is required.

Adequate cross ventilation should be provided and explosion proof fans may be required. All foodstuffs must be removed during application of the system.

**Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. If substrate and/or material temperature is above 90°F, Do Not apply material.**

### **IMPORTANT!**

*Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.*

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT **DUR-A-FLEX.COM** FOR THE LATEST VERSION