

DUR-A-SOLVE

DESCRIPTION

DUR-A-SOLVE is a unique combination of aromatic solvents, designed for use with Dur-A-Flex Epoxy products and for various uses around jobsites.

It is specifically formulated for use with blended DUR-A-GLAZE #4, DUR-A-GLAZE Novolac, and DUR-A-GARD Epoxy products, featuring an approximate flash point of 85°F as per a Closed Cup Test.

Generally, adding 3 - 9% of DUR-A-SOLVE to a mixed batch is all that is needed to produce desired viscosity. Adding DUR-A-SOLVE to blended Epoxy products will also extend the pot life and the curing time.

DUR-A-SOLVE may also be used as an all-purpose cleaning solvent for tools used with Dur-A-Flex materials, and as a lubricant for coving trowels when applying resinous cove material.

PACKAGING

DUR-A-SOLVE is available in 1 gallon cans, 5 gallon pails, and 50 gallon drums.

DANGER - USE WITH CAUTION

All solvents may be harmful or fatal if swallowed. These products are flammable or combustible. DUR-A-SOLVE vapors are harmful. Keep away from heat, sparks and open flame. Use only with adequate ventilation and provide an appropriate respirator mask. Avoid skin contact. If contact occurs, wash with soap and water. If splashed into eyes, lift eyelids, flush with clear water for 15 minutes, and call a physician for advice.

Follow the Safety Data Sheet for proper personal protective equipment to use when handling this product. Use only as directed. KEEP OUT OF REACH OF CHILDREN.

IMPORTANT!

Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT DUR-A-FLEX.COM FOR THE LATEST VERSION