

FIBERGLASS MAT

DESCRIPTION

DUR-A-FLEX FIBERGLASS MAT is a wall reinforcement product designed for use with DUR-A-FLEX DUR-A-WALL and DUR-A-WALL HP wall systems. DUR-A-FLEX FIBERGLASS MAT is engineered with a porous, open fiber design that allows coatings to flow through and bond with its reinforced glass mat fibers, as well as the underlying work surface for a smooth uniform finish.

PACKAGING

DUR-A-FLEX FIBERGLASS MAT is available in 36 in x 180 ft rolls (540 sq ft per roll).

CAUTION

Follow the Hazardous Materials Identification System labeling guide for proper personal protective equipment to use when handling this product. Use only as directed. **KEEP OUT OF REACH OF CHILDREN.** Before using any Dur-A-Flex products, be sure the Safety Data Sheet is read and understood.

TECHNICAL INFORMATION

Construction	Non-woven
Fiber Type	Fiberglass (E-glass)
Filament Designation	M-type per ASTM D578
Coating	Urea, polymer
Loss on Ignition	20.0%
Width	36 inches
Weight	1.10 lbs/100ft
Thickness	0.017 inch
Tensile Strength	Warp: 60 (lb/3-inch) Weft: 00 (lb/3-inch)

IMPORTANT!

Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT **DUR-A-FLEX.COM** FOR THE LATEST VERSION