

Cryl-A-Prime P101 SAFETY DATA SHEET

1. IDENTIFICATION

Product Identifier: Cryl-A-Prime P101

Recommended use: Floor Surfacing

Manufacturer Name: Dur-A-Flex, Inc.
95 Goodwin Street
East Hartford, CT 06108

Telephone number: 860-528-9838

Emergency phone number: 1-800- 424-9300 (CHEMTREC)

Date of Preparation: January 11, 2022

2. HAZARD(S) IDENTIFICATION

Classification:

Physical	Health
Flammable Liquid Category 2	Skin Irritation Category 2 Skin Sensitization Category 1 Specific Target Organ Toxicity Single Exposure Category 3 (Respiratory Irritation) Carcinogen Category 2

Labeling:

Danger!



Hazard statement(s)

Highly flammable liquid and vapor.
Causes skin irritation
May cause an allergic skin reaction
May cause respiratory irritation.
Suspected of causing cancer.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, sparks, open flames, and hot surfaces.
No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment
Use explosion-proof electrical, ventilating and lighting equipment.
Use only non-sparking tools.

Take precautionary measures against static discharge.
 Avoid breathing mist, vapors or spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing should not be allowed out of the workplace.
 Wear protective gloves, eye protection and face protection.
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical attention.
 Wash contaminated clothing before reuse.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 Call a POISON CENTER or doctor if you feel unwell.
 IF exposed or concerned: Get medical attention.
 In case of fire: Use water spray, carbon dioxide and foam to extinguish.
 Store in a well-ventilated place. Keep cool. Keep container tightly closed.
 Store locked up.
 Dispose of contents and container in accordance with local and national regulations.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Concentration
Methyl Methacrylate	80-62-6	60-80%
Acrylic Copolymer Resin	Proprietary	20-50%
Triethylene Glycol Dimethacrylate	109-16-0	1-5%
N,N-Dimethyl-p-toluidine	99-97-8	1-5%

The specific identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

Inhalation: Remove victim to fresh air. If breathing is difficult, have qualified personnel administer oxygen. If breathing has stopped, administer artificial respiration. Get medical attention.

Skin contact: Remove contaminated clothing. Wash skin thoroughly with soap and water. If irritation or other symptoms develop, get medical attention. Launder clothing before re-use.

Eye contact: Flush with large quantities of water for several minutes, holding the eyelids apart. Get medical attention if irritation persists.

Ingestion: If conscious, rinse mouth with water. Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Get medical attention.

Most important symptoms/effects, acute and delayed: May cause respiratory tract, eye and skin irritation. Prolonged or repeated contact may cause allergic skin reaction (skin sensitization). May cause cancer based on animals data.

Indication of immediate medical attention and special treatment, if necessary: If skin irritation or sensitization occurs, discontinue use and get medical attention.

5. FIRE-FIGHTING MEASURES

Suitable (and unsuitable) extinguishing media: Use water spray, carbon dioxide or dry chemical. Cool fire exposed containers with water.

Specific hazards arising from the chemical: Vapors are heavier than air and may travel to ignition source and flash back. Heat of fire may cause an exothermic auto polymerization reaction. Emits toxic fumes under fire conditions. Closed containers may explode due to pressure build up when exposed to extreme heat.

Special protective equipment and precautions for fire-fighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, and emergency procedures: Provide explosion-proof ventilation. Avoid contact with skin, eyes or clothing. Avoid breathing vapors. Wear appropriate protective clothing as described in Section 8. Eliminate all ignition sources.

Environmental precautions: Avoid release to the environment. Report releases as required by local, state and federal authorities.

Methods and materials for containment and cleaning up: Contain and collect with an inert absorbent. Place into an appropriate container for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling: Avoid contact with eyes, skin, and clothing. Avoid breathing vapors or mist. Wash thoroughly after handling. Wear protective clothing and equipment as described in Section 8. Use with adequate ventilation. Ground container when pouring. Keep away from heat, sparks, flames and all sources of ignition. Do not expose to direct sunlight. Empty containers retain product residues and can be hazardous. Follow all SDS precautions when handling empty containers.

Conditions for safe storage, including any incompatibilities: Store in a cool, dry, well ventilated area. Keep container tightly closed when not in use. Do not store in direct sunlight. Prevent moisture contact. Protect from physical damage. Keep away from oxidizers and other incompatible materials.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure guidelines:

Methyl Methacrylate	100 ppm TWA OSHA PEL 50 ppm TWA ACGIH TLV 100 ppm ACGIH TLV STEL
Acrylic Copolymer Resin	None Established
Triethylene Glycol Dimethacrylate	None Established
N,N-Dimethyl-p-toluidine	0.5 ppm TWA AIHA WEEL

Appropriate engineering controls: Use with adequate general or local exhaust ventilation to maintain exposures below occupational exposure limits. Use explosion-proof equipment where required.

Personal Protective Equipment:

Respiratory protection: None required with adequate ventilation. An approved air-purifying respirator with an organic vapor cartridge may be permissible under certain limited circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. Selection and use of respiratory equipment must be in accordance with appropriate regulations and good industrial hygiene practice.

Skin protection: Wear impervious gloves such as nitrile rubber or other impervious gloves.

Eye protection: Wear safety chemical goggles when the possibility exists for eye contact due to splashing or spraying material.

Other: Wear impervious clothing if needed to prevent any contact with this product, such as gloves, apron, boots, or whole body suit.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance (physical state, color, etc.): Moderately turbid fluid with a sweet ester odor

Odor: Sweet ester odor

Odor threshold: Not available	pH: Not available
Melting Point/Freezing Point: Not available	Boiling Point: 212°F / 100°C
Flash point: 50 °F / 10°C (Setaflash)	Evaporation rate: >1 (butyl acetate = 1)
Flammability (solid, gas): Not applicable	
Flammable limits: LEL: 2.1% (Methyl Methacrylate)	UEL: 12.5% (Methyl Methacrylate)
Vapor pressure: 35 mmHg @ 20°C (Methyl Methacrylate)	Vapor density: >1
Relative density: ~1	Solubility(is): 16 g/L (in water)
Partition coefficient: n-Octanol/water: Not applicable	Auto-ignition temperature: >500°F / 260°C (Methyl Methacrylate)
Decomposition temperature: Not available	Viscosity: Not available
Self accelerating polymerization temperature (SAPT): 55°C	

10. STABILITY AND REACTIVITY

Reactivity: Polymerization can occur.

Chemical stability: Stable when stabilized. The product is unstable at elevated temperatures and pressures.

Possibility of hazardous reactions: Methyl methacrylate can undergo hazardous polymerization if exposed to excessive heat, peroxides and polymerization catalysts.

Conditions to avoid: Avoid heat, sparks and open flames.

Incompatible materials: Avoid contact with oxidizing agents, reducing agents, peroxides and polymerization catalysts.

Hazardous decomposition products: Thermal decomposition may produce carbon oxides, toxic fumes and hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Inhalation: May cause respiratory tract irritation with coughing, mucous production and shortness of breath. Methyl methacrylate has been shown to cause irritation of the upper respiratory tract in studies with laboratory animals.

Ingestion: Swallowing may cause gastrointestinal irritation, nausea and diarrhea.

Skin contact: Causes skin irritation. Methyl methacrylate has been shown to cause severe irritation when tested undiluted on rabbit skin. Causes skin sensitization. Cases of contact dermatitis has been reported in workers exposed to methyl methacrylate.

Eye contact: May cause eye irritation. Methyl methacrylate has been shown to cause mild irritation to the conjunctiva in animal studies.

Chronic effects from short- and long-term exposure: In subchronic inhalation studies with methyl methacrylate, systemic toxic effects were seen in rats to the liver, kidney, brain, spleen and bone marrow >1000 ppm. Oral administration of methyl methacrylate to rats resulted in a NOAEL of 200 mg/kg.

Reproductive Toxicity: This product is not expected to cause adverse reproductive or developmental effects. Methyl methacrylate did not cause reproductive effects on male fertility when animals were exposed to 9000 ppm. No teratogenicity, embryotoxicity or fetotoxicity has been observed at exposure levels up to and including 2028 ppm

Sensitization: Methyl methacrylate and triethylene glycol dimethylacrylate have been shown to cause sensitization in a mouse local lymphnode assays.

Mutagenicity: Methyl methacrylate was negative in sister chromatid exchange assay in mammalian cells and in a vivo chromosome aberration assay.

Carcinogenicity: None of the components are listed as a carcinogen by IARC, NTP, ACGIH or OSHA. In a 2 year NTP carcinogenicity study N,N-dimethyl-p-toluidine was administered by gavage to male and female mice and rats. Results included increased incidences of nonneoplastic lesions of the liver and nasal cavity in male and female rats and mice; the kidney in male and female rats; the spleen and bone marrow in male and female rats and female mice; the lung in male and female mice; the forestomach in male rats and female mice; the mesenteric lymph node in male rats and female mice; and the olfactory lobe in male and female mice.

Acute Toxicity Values: No toxicity data for the product. Acute Toxicity Estimate: Oral rat LD50 6174 mg/kg
Methyl Methacrylate: Oral rat LD50 7800 mg/kg; Inhalation rat LC50 3750 mg/L/8 hr; Dermal rabbit LD60 >5000 mg/kg

Acrylic Copolymer Resin: No toxicity data available

Triethylene Glycol Dimethacrylate: Dermal rabbit LD50 > 2000 mg/kg

N,N-Dimethyl-p-toluidine: Oral rat LD50 139 mg/kg; Inhalation rat LC50 1400 mg/m³/4 hr; Dermal rabbit LD50 > 2000 mg/kg; ;

12. ECOLOGICAL INFORMATION

Ecotoxicity:

Methyl Methacrylate: 96 hr LC50 Pimephales promelas 130 mg/L; 24 hr LC50 daphnia magna 1760 mg/L

Acrylic Copolymer Resin: No data available

Triethylene Glycol Dimethacrylate: 96 hr LC50 Danio rerio 16.4 mg/L; 72 hr EC50 Pseudokirchnerella subcapitata > 100 mg/L

N,N-Dimethyl-p-toluidine: 96 hr LC50 Pimephales promelas 46 mg/L; 48 hr daphnia magna 15.259 mg/L; 72 hr EC50 Pseudokirchneriella subcapitata 24.37002 mg/L

Persistence and degradability: Methyl methacrylate, N,N-dimethyl-p-toluidine and triethylene glycol dimethacrylate are readily biodegradable.

Bioaccumulative potential: Methyl methacrylate has a BCF of 2.97.

Mobility in soil: Methyl methacrylate has a high mobility in soil.

Other adverse effects: None known.

13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

	UN Number	Proper shipping name	Hazard Class	Packing Group	Environmental Hazard
DOT	UN1247	Methyl Methacrylate Monomer, Stabilized	3	II	None
TDG	UN1247	Methyl Methacrylate Monomer, Stabilized	3	II	None
IMDG	UN1247	Methyl Methacrylate Monomer, Stabilized	3	II	None
IATA	UN1247	Methyl Methacrylate Monomer, Stabilized	3	II	None

Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable – product is transported only in packaged form.

Special precautions: None known

15. REGULATORY INFORMATION

CERCLA: This product has a Reportable Quantity (RQ) of 1250 lbs. (based on the RQ for Methyl Methacrylate of 1000 lbs). Releases above the RQ must be reported to the National Response Center. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

SARA Hazard Category (311/312): Acute Health, Chronic Health, Fire Hazard, Reactive Hazard

SARA 313 Information: This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Methyl Methacrylate	80-62-6	60-80%
---------------------	---------	--------

California Proposition 65

This product contains the following chemicals known to the State of California to cause cancer or reproductive toxicity (birth defects):

N,N-Dimethyl-p-toluidine	99-97-8	1-5%	Cancer
--------------------------	---------	------	--------

EPA TSCA Inventory: All of the ingredients in this product are listed on the EPA TSCA Inventory.

CANADA:

Canadian WHMIS Classification: Class B-2 (Flammable Liquid) Class D Division 2 Subdivision B (Toxic Material Causing other Toxic Effects)

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

16. OTHER INFORMATION

NFPA Rating: Health = 2 Flammability = 3 Instability = 2
HMIS Rating: Health = 2 Flammability = 3 Physical Hazard = 2

SDS Revision History: Converted to GHS format. All sections revised.

Date of preparation: July 17, 2014

Date of last revision: January 11, 2022

The above information is accurate to the best of our knowledge. However, since data, safety standards, and government regulations are subject to change and the conditions of handling and use, or misuse, are beyond our control, Dur-A-Flex, Inc. **MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, WITH RESPECT TO THE COMPLETENESS OR CONTINUING ACCURACY OF THE INFORMATION CONTAINED HEREIN AND USE.**