

POLY-CRETE URETHANE FLOORING w/COLOR-FAST TOPCOAT

POLY-CRETE WR (MUST BE WET PRIMED w/TF)

ELAST-O-COAT

OPEN WEEP HOLES

FLOOR DRAIN / FLOOR SINK (TYP)

COMPRESSION FLANGE

PEASTONE TO KEEP WEEP HOLES CLEAR (1" BERM)

HYDRAULIC CEMENT TO SECURE DRAIN BODY FULLY GROUTED VOIDS (EXPANSION TYPE TO IMMOBILIZE FIXTURE)

1-1/2" +/-

DOUBLE CORE

EXISTING SLAB

4 BAND CLAMPS FOR ALL WET PIPES (2 BAND CLAMPS NOT ALLOWED)

METAL STUD FRAMING & DUROCK FORM / BOX

CAULK OR INSULATE TO HOLD HYDRAULIC CEMENT (FLOWABLE) (NOTE: A LOOSE FLOWABLE MIX IS REQUIRED)



NOTE: 1st COAT OF ELAST-O-COAT NEEDS TO BE BETWEEN THE FLANGE



**DUR-A-FLEX**  
INNOVATION FROM THE FLOOR UP

[www.dur-a-flex.com](http://www.dur-a-flex.com)

860-528-9838

**TITLE** POLY-CRETE MD, MDB, MDC, MDQ  
DRAIN w/ELAST-O-COAT FOR SUSPENDED SLAB DETAIL

**DATE** 5/15

**SCALE** NTS

**DWG NO.** PCMD-24

**PROJECT**