

# POLY-CRETE® HF



**Body Coat** - Pigmented Poly-Crete HF Mortar (optional Dur-A-Grit for added slip resistance)

**Prepared Substrate** - Concrete Surface Profile (CSP) of 3-6

## SYSTEM OVERVIEW

**POLY-CRETE HF** is a 100% solids, aromatic, cementitious urethane concrete coating system. It is a solid color, trowel-applied floor system designed to withstand aggressive chemical and thermal attack while providing abrasion resistance. Its coefficient of thermal expansion is similar to concrete, making it very resistant to thermal shock.

## FEATURES & BENEFITS

### • Wear / Chemical Resistance

High quality system for superior wear and chemical resistance

### • Thermal Shock Resistant

Usable in harsh environments with high thermal cycling or rapid changes in temperature

### • Abrasion Resistant

Offering protection from unsightly scratches

### • Strength

Offering the highest level of durability

### • Non Slip

Offering traction and promoting safety

## COMMON USE SITES

- Bottling Areas
- Manufacturing Areas
- Food Processing Areas



## COLORS

Available in standard solid color topcoats. For a full list of available colors visit [DUR-A-FLEX.COM](http://DUR-A-FLEX.COM)



BLUE\*



GREY



CHARCOAL



RED



DARK GREY



GREEN\*



CHESTNUT

Poly-Crete HF features a matte finish.



### IMPORTANT!

*Before using DUR-A-FLEX products, read and understand its accompanying Safety Data Sheet & Application Instructions for important safety information.*

STANDARD TERMS AND CONDITIONS OF SALE, INCLUDING STANDARD WARRANTY APPLY - VISIT [DUR-A-FLEX.COM](http://DUR-A-FLEX.COM) FOR THE LATEST VERSION

210430



**DUR-A-FLEX**  
INNOVATION FROM THE FLOOR UP

CONNECTICUT | GEORGIA | ILLINOIS | CALIFORNIA  
TOLL FREE 800-253-3539 | 860-528-9838 | [DUR-A-FLEX.COM](http://DUR-A-FLEX.COM)